

DECLARATION OF PERFORMANCE No. 100-15

(according to REGULATION (EU) No 305/2011 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2011)

1. Unique identification code of the product-type:		SONATA QUADRILLE	
2. Type of the construction product:		bitumen shingles with mineral reinforcement, type 6S4X21 , produced in accordance with EN 544:2011	
3. Intended use or uses of the construction product:		intended to be laid as discontinuous covering for pitched roofs with pitch $\ge 12^{\circ}$ and / or wall cladding where the watertightness of the system is ensured by overlapping, according to the manufacturer's installation instructions	
4. Name and contact address of the manufacturer:		UAB Mida LT	
		Gamyklos g. 19, LT-96155 Gargzdai, Lithuania Tel.:+370-46455356; info@mida.lt; www.mida.lt	
5. System or systems of assessment and verification:		System 4; reaction to fire and external fire performance - System 3	
6.1. Harmonised European Norm:		EN 544:2011	
6.2. Notified Body Nr. 1796 Priešgaisrinės apsaugos ir gelbėjimo departamento prie Vidaus reikalų ministerijos Gaisrinių tyrimų centras, Lithuania:		performed reaction to fire tests, external fire exposure to roofs tests and issued classification reports	
6.3. Notified Body RISE Fire Research AS, Norway. Norwegian accreditation test 014:		performed external fire exposure to roof covering tests (test methode CEN/TS 1187:2012, test 2) and issued classification report	
7. Declared performance		·	
Essential characteristics	Performance		
		Performance	Harmonised technical specification
Dimensions of shingles (width / height)	1000	D mm (± 3 mm) / 317 mm (± 3 mm)	
	1000		
Mass of bitumen	100(0 mm (± 3 mm) / 317 mm (± 3 mm)	
Mass of bitumen External fire performance	1000	0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m²	
Mass of bitumen External fire performance	1000	0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m² B _{ROOF} (t1); B _{ROOF} (t2)	
Mass of bitumen External fire performance Reaction to fire		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m² B _{ROOF} (t1); B _{ROOF} (t2)	
Mass of bitumen External fire performance Reaction to fire Mechanical resistance:		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m² B _{ROOF} (t1); B _{ROOF} (t2) class E	
Mass of bitumen External fire performance Reaction to fire Mechanical resistance: tensile strength (in direction of the shingle		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m ² B _{ROOF} (t1); B _{ROOF} (t2) class E 850 N/50 mm (± 200 N/50mm) /	
Mass of bitumen External fire performance Reaction to fire Mechanical resistance: tensile strength (in direction of the shingle width / height) nail shank resistance		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m ² B _{ROOF} (t1); B _{ROOF} (t2) class E 850 N/50 mm (± 200 N/50mm) / 600 N/50 mm (± 200 N/50mm)	specification
Mass of bitumen External fire performance Reaction to fire Mechanical resistance: tensile strength (in direction of the shingle width / height) nail shank resistance Durability:		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m ² B _{ROOF} (t1); B _{ROOF} (t2) class E 850 N/50 mm (± 200 N/50mm) / 600 N/50 mm (± 200 N/50mm) 220 N (± 100 N) 	specification
Mass of bitumen External fire performance Reaction to fire Mechanical resistance: tensile strength (in direction of the shingle width / height) nail shank resistance Durability:		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m ² B _{ROOF} (t1); B _{ROOF} (t2) class E 850 N/50 mm (± 200 N/50mm) / 600 N/50 mm (± 200 N/50mm) 220 N (± 100 N)	specification
Mass of bitumen External fire performance Reaction to fire Mechanical resistance: tensile strength (in direction of the shingle width / height) nail shank resistance Durability: Water absorption Flow resistance at elevated temperature		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m ² B _{ROOF} (t1); B _{ROOF} (t2) class E 850 N/50 mm (± 200 N/50mm) / 600 N/50 mm (± 200 N/50mm) 220 N (± 100 N) 	specification
Mass of bitumen External fire performance Reaction to fire Mechanical resistance: tensile strength (in direction of the shingle width / height) nail shank resistance Durability: Water absorption Flow resistance at elevated temperature Adhesion of mineral granules		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m ² B _{ROOF} (t1); B _{ROOF} (t2) class E 850 N/50 mm (± 200 N/50mm) / 600 N/50 mm (± 200 N/50mm) 220 N (± 100 N) < 1,5 % ≤ 2 mm at 100 °C	specification
tensile strength (in direction of the shingle width / height) nail shank resistance Durability: Water absorption		0 mm (± 3 mm) / 317 mm (± 3 mm) ≥1300 g/m ² $B_{ROOF}(t1); B_{ROOF}(t2)$ class E 850 N/50 mm (± 200 N/50mm) / 600 N/50 mm (± 200 N/50mm) 220 N (± 100 N) <pre> </pre> </td <td>specification</td>	specification

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of UAB Mida LT by:

Chief Technologist Živilė Paulauskaitė

(name and function) Gargždai, 2022 02 01 (place and date of issue) UAB * "Mida LT" + UMB JSC UMB JSC UMB